

PREPARING FOR YOUR INSTALL

- REMOVE ALL ITEMS *UNDER* YOUR SINK CABINET
- KNOW THE LOCATION OF YOUR MAIN WATER VALUE, **TURN OFF SINK WATER LINES UNDER SINK**. IF DRIPPING APPEARS, THE VALVE MIGHT NEED TO BE REPLACED.
- **REMOVE TOP DRAWERS AND CLEAR OFF YOUR COUNTERTOP!**
- PREPARE AND PROTECT DRAWERS AND BOTTOM CABINET, AS LIGHT DUST FROM THE INSTALLATION WILL END UP IN CORNERS ETC. INSTALLERS WILL LIGHTLY CLEAN UP AFTER INSTALL. **HOMEOWNER RESPONSIBLE FOR FINAL CLEANING.**
- HAVE YOUR NEW FAUCET ONSITE
- OLD SINK WILL BE LEFT FOR RE-CONNECTION; SOME PARTS CAN BE REUSED. HOMEOWNER RESPONSIBLE FOR DISPOSAL OF OLD SINK.
- AFTER INSTALL, COUNTERS NEED TO SET AND DRY FOR AT LEAST 4 TO 6 HOURS BEFORE USAGE
- **MOVE ALL VEHICLES FROM YOUR DRIVEWAY**. STONE CUTTING WILL TAKE PLACE IN DRIVEWAY; STONE GRIT WILL BE FLOATING IN THE AIR.
- **SECURE YOUR PETS**, WE WILL BE IN AND OUT DURING INSTALLATION
- CHUCK WILL EMAIL “HOW TO CARE FOR YOUR STONE”